



FULL BODY HARNESS



MODEL NO.: SH-FBH-11
 One Dorsal D Ring
 Thigh and Chest Straps
 Dual Colour Scheme
 Conforms to EN 361:2002



MODEL NO.: SH-FBH-12
 One Dorsal D Ring
 2 Chest textile loops
 Shoulder and Thigh Straps
 Dual Colour Scheme
 Conforms to EN 361:2002



MODEL No.: SH-FBH-21
 One Dorsal D Ring
 Shoulder and Thigh Straps
 Dual Colour Scheme
 Conforms to EN 361:2002



MODEL NO.: SH-FBH-24
 One Dorsal D Ring
 One Chest D Rings
 Shoulder and Thigh Straps
 Dual Colour Scheme
 Conforms to EN 361:2002



MODEL NO.: SH-FBH-23
 One Dorsal D Ring
 2 Chest D Rings
 Shoulder and Thigh Straps
 Dual Colour Scheme
 Conforms to EN 361:2002




MODEL NO.: SH-FBH-22
 One Dorsal D Ring
 2 Chest textile loops
 Shoulder and Thigh Straps
 Dual Colour Scheme
 Conforms to EN 361:2002



MODEL NO.: SH-FBH-25
 One Dorsal D Ring
 One Chest D Rings
 Extension Rescue Strap
 Shoulder and Thigh Straps
 Dual Colour Scheme
 Conforms to EN 361:2002 & EN 1497



MODEL NO.: SH-FBH-42
 Harness Incorporated with work
 Positioning Belt
 For both Fall Arrest & Work Positioning
 Conforms to EN 361:2002, 358:1999



WIDE COMFORT PAD

MODEL NO.: SH-WPB-01
 Fully adjustable with Lateral D-Rings
 Tool holding webbing loops
 Wide pad for Extra Comfort
 Available in Medium, Large and Extra Large
 Conforms to EN 359:1999



ENERGY ABSORBER

MODEL NO.: SH-EA-300
 44mm Wide Webbing
 Shrink wrapped and reduces the
 impact of fall
 Special Polyamide Core Tear
 Webbing
 Additional Length of about 110 cm
 Clear Protective Covering
 Conforms to EN 355:2002



HOOKS

MODEL NO.: SH-SSH-131
 Forged Alloy Steel
 Minimum Breaking Strength of 23KN
 Conforms to EN 362:2004



MODEL NO.: SH-SSK-112
 Alloy Steel
 Minimum Breaking Strength of 23KN
 Conforms to EN 362:2004



MODEL NO.: SH-RG-03
 Rope Grab



MODEL NO.: SH-SSH-121
 Alloy Steel
 Minimum Breaking Strength of 23KN
 Conforms to EN 362:2004

These Hooks Can Be Supplied With Any Of The Rope Lanyards & Webbing Lanyards.

ROPE LANYARDS

MODEL NO.: SH-TRL-204



TWISTED ROPE LANYARDS

12mm dia Polyamide Twisted Rope
 Coloured Tracer
 Abrasion Resistant Thimble
 Strong Transparent Covering Sleeve
 Minimum Breaking Strength of 22KN
 Available in 1.0m, 1.5m, 1.8m, 2.0m
 Conforms to EN354:2002
 Also supplied with any other hook on special request.

MODEL NO.: SH-BRL-381



KERNMANTLE ROPE LANYARDS

12mm dia Polyamide Kernmantle Rope
 Coloured Tracer
 Abrasion Resistant Thimble
 Strong Transparent Covering Sleeve
 Minimum Breaking Strength of 22KN
 Available in 1.0m, 1.5m, 1.8m, 2.0m
 Conforms to EN354:2002

MODEL NO.: SH-TRL-304



MODEL NO.: SH-BRL-281



WEBBING LANYARDS

MODEL NO.: SH-WL-221



Webbing Lanyards

44mm wide Polyester Webbing • Minimum Breaking Strength of 22 KN
 Available in 1.0m, 1.5m, 1.8m, 2.0m • Conforms to EN354:2002
 Also supplied with any other hook on special request.

MODEL NO.: SH-WL-321



MODEL NO.: SH-WL-228



MODEL NO.: SH-WL-227



LEGACY OF EXCELLENCE

E-23,24, Site 1, UPSIDC, Industrial Area, Unnao- 209801, Uttar Pradesh (India)
 Phone: +91-515-2829701 • Fax: +91-515 2829190
 E Mail: contact@panaceasafety.com • Website: www.panaceasafety.com



PANACEA
 SAFETY SOLUTIONS

CE 0321 CERTIFIED BY SATRA TECHNOLOGY CENTRE